



Insuloid Cable Ties

Standard Ties

The Insulok range of cable ties is moulded in Nylon 66. Standard colours black and neutral.

- One piece, all plastic (no metal pins or fasteners).
- Quick, simple fixing by hand or with tensioning tools.
- Low cost components.
- Manufactured to the quality control requirements of BS 5750 Part 2 and the U.S. Mil. Spec. 23190.

The 'T' range of ties is listed by the U.S. Defence Department and meets the dimensional requirements of Drawing MS 3367.

Approvals

American Mil. Spec. 23190 U.L. (Underwriters Laboratory) Defence Standard AQAP-9 Lloyds Register of Shipping Bureau Veritas Ford Q101.

Ref No.	Nom. Overall Length (mm)	Strap Width (mm)	Min Tensile Strength (kg)	Max Cable Bundle Dia (mm)
T18R	100	2.5	8.1	16
LK2	120	2.5	8.1	16
T30R	150	3.5	13.6	35
T50R	200	4.6	22.7	50
LK2A	270	4.8	22.7	73
T120I	300	8.6	45.5	70
T50L	385	4.6	22.7	109
T120R	390	7.6	54.4	108
LK5	540	13.0	113.4	152

Cable Tray Fixing Ties

These simple, neat ties provide a permanent answer to the problem of fixing cable to cable trays. The one piece moulding in tough, flexible Nylon 66, snaps apart to slot into cable trays.

Ref No.	Nom. Overall Length (mm)	Strap Width (mm)	Min Tensile Strength (kg)	Max Cable Bundle Dia (mm)
CTF 120	315	7.6	54.5	-
CTF 250	360	13.0	113.4	-

Other ties available include releasable and stainless steel types. Self adhesive bases and banding strap also stocked.

