

PRYSMIAN (B) MultiCleat Plus Range

Multicleat | Multistrap System ® Patent No 2082242

- 24 to 110mm diameter cables in trefoil groups in 10 sizes.
- Exceptional overlapping ranges.
- Non-magnetic materials used throughout, except for cast iron bases.
- Multicleat bases available as either single or two fixing designs.
- Operating temperature -60°C to +100°C.
- Multicleat bases available in cast iron, aluminium alloy or stainless steel with various finishes.



Suitable for single or trefoil cable formations.

Single Cable Dim (mm)	Std Ref No.	Heavy Duty Ref No.
85 - 110	-	378AB29
105 - 120	378AB09	378AB59

Trefoil Cable Dim (mm)	Std Ref No.	Heavy Duty Ref No.
24 - 34	378AB01	378AB51
30 - 41	378AB02	378AB52
37 - 47	378AB03	378AB53
43 - 54	378AB04	378AB54
50 - 60	378AB05	378AB55
56 - 67	378AB06	378AB56
63 - 73	378AB07	378AB57
69 - 80	378AB08	378AB58
72 - 85	-	378AB36
82 - 95	-	378AB37
92 - 105	-	378AB38
102 - 115	-	378AB39
112 - 125	-	378AB40
122 - 135	-	378AB41
132 - 145	-	378AB42

Multicleat Plus - Standard & Heavy Duty (Epoxy Coated Aluminium Base) ®

Suitable for single or trefoil cable formations.

Cable Dim (mm)	Std Ref No.	Duty Ref No.
85 - 110	-	378AD29
105 - 120	378AD09	378AD59

Trefoil Cable Dim (mm)	Std Ref No.	Heavy Duty Ref No.
24 - 34	378AD01	378AD51
30 - 41	378AD02	378AD52
37 - 47	378AD03	378AD53
43 - 54	378AD04	378AD54
50 - 60	378AD05	378AD55
56 - 67	378AD06	378AD56
63 - 73	378AD07	378AD57
69 - 80	378AD08	378AD58
102 - 115	-	378AD39

Multicleat Plus - Standard & Heavy Duty (Stainless Steel Base - Single Bolt) ® Suitable for single or trefoil cable formations.

	Single Cable Dim (mm)	Std Ref No.	Heavy Duty Ref No.
l	105 - 120	378PF09	378PF59

Trefoil Cable Dim (mm)	Std Ref No.	Heavy Duty Ref No.
24 - 34	378PF01	378PF51
30 - 41	378PF02	378PF52
37 - 47	378PF03	378PF53
43 - 54	378PF04	378PF54
50 - 60	378PF05	378PF55
56 - 67	378PF06	378PF56
63 - 73	378PF07	378PF57
69 - 80	378PF08	378PF58

Multistrap ®

- A multistrap is a strap complete with a tensioning clip, securing pin and winding key all made from highly corrosion resistant non-magnetic stainless steel.
- They are used as an intermediate restraint between Multicleats.
- They may be used to bind cables together.
- Improved strap design shorter, thicker strap with safer rounded edges.
- Multistraps are available in two strengths:

Standard Duty - designed to have 2 loops of 0.38mm thick strap around the cables. **Heavy Duty** - designed to have 3 loops of 0.38mm thick strap around the cables.



Multistrap Plus - Standard & Heavy Duty

For use as an intermediate support between multicleats.

Trefoil Cable Dim (mm)	Std Ref No.	Heavy Duty Ref No.
24 - 34	378AB01	378AB51
30 - 41	378AB02	378AB52
37 - 47	378AB03	378AB53
43 - 54	378AB04	378AB54
50 - 60	378AB05	378AB55
56 - 67	378AB06	378AB56
63 - 73	378AB07	378AB57
69 - 80	378AB08	378AB58

Trefoil Cable Dim (mm)	Std Ref No.	Heavy Duty Ref No.
72 - 85	-	378AB36
82 - 95	-	378AB37
92 - 105	-	378AB38
102 - 115	-	378AB39
112 - 125	-	378AB40
122 - 135	-	378AB41
132 - 145	-	378AB42
92 - 105 102 - 115 112 - 125 122 - 135	- - -	378AB38 378AB39 378AB40 378AB41

LSOH Liners

LSF liners can be supplied for use with Multistrap.

For Styles	Ref No.
01 - 04 inc.	377LSF01
01 - 04 inc. 51 - 54 inc.	
05 - 09 inc.	
36 - 37 inc.	
55 - 59 inc.	377LSF02