



## Cable Cleats Selection Chart

Cable Type	CABLE SPEC.		CLEATS					Horizontal Spacing of Cleats (mm)
	Conductor Area (mm <sup>2</sup> )	No. Of Cores	Telcleat Black Polythene 385AA- 385 LSF	Hookcleat Alum 371AA-	Nylon 384AA-	Claw & 2 Bolt Cleats 370BA- *	Ranger Cleat High Impact Polystyrene 382AA-	
1.5	2	01	-	-	-	01	-	300
	3	01	-	-	-	01	-	300
	4	01	-	-	-	01	01	300
	7	02	-	-	-	02	01	350
	12	03	-	-	-	03	02	350
	19	04	-	-	-	04	03	400
	27	05	-	-	01	05	03	400
	37	06	05	01	01	06	04	400
2.5	2	01	-	-	-	02	01	300
	3	01	-	-	-	02	01	300
	4	02	-	-	-	02	01	300
	7	02	-	-	-	03	01	350
	12	04	-	-	-	04	03	400
	19	05	-	01	-	05	03	400
	27	06	05	01	-	06	04	400
	37	06	05	01	01	06	04	400
4	2	02	-	-	-	02	01	350
	3	02	-	-	-	02	01	350
	4	03	-	-	-	03	01	350
6	2	03	-	-	-	03	01	350
	3	03	-	-	-	03	01	350
	4	04	-	-	-	04	02	350
10	2	04	-	-	-	04	02	400
	3	04	-	-	-	04	02	400
	4	04	-	-	-	05	03	400
16	2	04	-	-	-	03	03	400
	3	04	-	-	-	05	03	400
	4	05	05	-	-	06	03	400
25	2	04	-	-	-	04	03	400
	3	05	-	01	-	05	03	400
	4	05	05	01	-	06	04	400
35	2	05	-	01	-	05	04	400
	3	05	05	01	-	06	04	400
	4	05	05	01	-	06	04	400
50	2	05	05	01	-	06	03	400
	3	06	05	01	-	06	04	400
	4	06	05	01	-	06	04	400
70	2	06	05	01	-	06	04	400
	3	06	06	01	-	07	04	400
	4	07	06	02	-	07	04	400
95	2	06	06	01	-	07	04	400
	3	07	06	01	-	07	04	400
	4	08	07	02	-	08	05	600
120	2	07	06	02	-	07	04	400
	3	07	07	02	-	08	05	400
	4	08	08	03	-	09	05	600
150	2	07	07	02	-	08	05	400
	3	08	08	03	-	09	05	600
	4	-	09	03	-	10	05	600
185	2	08	08	03	-	09	05	600
	3	08	08	03	-	09	05	600
	4	-	09	04	-	10	06	750
240	2	08	08	03	-	09	05	600
	3	-	09	03	-	10	06	750
	4	-	10	04	-	11	06	900
300	2	-	09	04	-	10	06	750
	3	-	10	04	-	11	06	750
	4	-	11	05	-	12	06	900
400	2	-	10	04	-	11	06	-
	3	-	11	05	-	12	06	-
	4	-	12	06	-	13	06	-

**1kV XLPE ARMoured CABLES TO BS 5467**

\* Two Bolt cleats from 370BA10.

*Details on cleats for cable in trefoil & voltages other than 1kV available on request. The recommendations above are given in good faith, but the dimensions of cable vary with manufacturing tolerances and we suggest that the cable diameter is measured where possible before purchasing cleats.*