



3M Cold Shrink System

QT111 Terminations

One piece silicone rubber.



6.6kV / 11kV

Indoor, Single Core, Polymeric, Copper Tape Screen, Lead Sheaths and/or Aluminium Wire Armoured.

Kit Ref	Cable Range mm ²
92-EP623-1	50 - 95
92-EP633-1	120 - 150
92-EP643-1	185 - 400
92-EP653-1	500 - 630

Indoor, Three Core, Polymeric, Copper Tape Screen/Armoured.

Kit Ref	Cable Range mm ²
7621 - T95-3W	16 - 50
7623 - T95-3W	70 - 120
7624 - T95-3W	150 - 300

Indoor, 11kV, Single Core, Polymeric, Copper Wire Screen.

Kit Ref	Cable Range mm ²
92-EP621-1	50 - 95
92-EP631-1	120 - 400
92-EP641-1	500 - 630
92-EP651-1	630 - 1000

Outdoor, Single Core, Polymeric, Copper Tape Screen, Lead Sheaths and/or Aluminium Wire Armoured.

Kit Ref	Cable Range mm ²
92-EP623-2	50 - 95
92-EP633-2	120 - 150
92-EP643-2	185 - 400
92-EP653-2	500 - 630

Outdoor, Three Core, Polymeric, Copper Tape Screen/Armoured.

Kit Ref	Cable Range mm ²
7691 - S4-3W	16 - 50
7692 - S4-3W	70 - 120
7693 - S4-3W	150 - 300

Outdoor, 11kV, Single Core, Polymeric, Copper Wire Screen.

Kit Ref	Cable Range mm ²
92-EP621-2	50 - 95
92-EP631-2	120 - 400
92-EP641-2	500 - 630

19kV / 33 (36) kV

Indoor/Outdoor, 33kV, Single Core, Polymeric, Copper Wire Screen.

Kit Ref	Cable Range mm ²
94-EP610-2	35 - 120
94-EP620-2	50 - 150
94-EP630-2	120 - 300
94-EP640-2	240 - 630

Indoor/Outdoor, Single Core, Polymeric, Copper Tape Screen, For Mechanical Connectors.

Kit Ref	Cable Range mm ²
94-EP611-2	25 - 120
94-EP621-2	70 - 240
94-EP631-2	185 - 400
94-EP641-2	400 - 630

Indoor/Outdoor, 33kV, Single Core, Polymeric, Copper Wire Screen, Aluminium Wire Armoured.

Kit Ref	Cable Range mm ²
94-EP612-2	50 - 120
94-EP622-2	70 - 240
94-EP632-2	185 - 400
94-EP640-2	400 - 630

24kV / 52kV and 72kV versions available.