



3M Termination Accessories

3M Cold Applied Barrier Boots 11kV

Inline - Part Number MB63.



3M Cold Applied 'Flexy' Barrier Boots

Inline/Right Angle - Part Number 92-EE717-1.

3M Cable Box Extension Glands

With cold applied protection sleeve.



Part Number	Diameter Range (mm)
THG1	36 - 65mm
THG2	53 - 94mm

3M 11kV Earthbonding Kit

Part Number	Application	Rating
SBT1	11kV Paper Cable 95 - 185	3kV / 3 Seconds
SBT2	11kV Paper Cable 95 - 185	7kV / 3 Seconds
SBT3	11kV Paper Cable 95 - 185	13.1kV / 3 Seconds
SBT4	11kV Paper Cable 240 - 400	3kV / 3 Seconds
SBT5	11kV Paper Cable 240 - 400	7kV / 3 Seconds
SBT6	11kV Paper Cable 240 - 400	13.1kV / 3 Seconds



3M Constant Force Springs

Ref	Minimum Diameter (mm)	Maximum Diameter (mm)
CFS 59	4.0	10.0
CFS 60	9.0	15.0
CFS 61	14.0	22.0
CFS 62	18.5	29.0
CFS 63	23.5	37.0
CFS 64	31.0	50.0
CFS 65	44.0	70.0
CFS 66	58.0	94.0

