



## Techlube Biodegradable Water Based Lubricants

- Underground Power & Telecom cable placement lubricants
- Duct pre-lubrication to reduce friction & risk in difficult pulls
- “String & Cling” consistency = perfect adhesion onto cable in wet weather & resistance to wash off in water filled ducts
- Compatibility tested with cable jacket materials and jointing accessories
- Techlube products retain duct lubrication for several months assisting additional cable pulls to same duct
- Non flammable
- Biodegradable & non toxic for environment and staff safety
- Several formulations (HD, Multi, PHD, M, FO) to match your exact need



Product Code	Description	Units Sold By
TLHD/20L-GB/DE	Techlube HD 20 Litre Bucket	Each
TLHD/PLB-GB/DE	Techlube HD 2 Litre Prelube Bags	10 / Bucket
TLPHD/20L-GB/DE	Techlube PHD 20 Litre Bucket	Each
TLPHD/1L-GB/DE	Techlube PHD 1 Litre Bottle	12 / Case
TLM/20L-GB/DE	Techlube M 20 Litre Bucket	Each
TLMULTI/20L-GB/DE	Techlube Multi 20 Litre Bucket	Each
TLFO/20L-GB/DE	Techlube FO 20 Litre Bucket	Each
TLFO/1L-GB/DE	Techlube FO 1 Litre Bottle	12 / Case

### Techlube Range

- HD** Heavy duty lubricant for heavy cables and difficult pulls. Available in buckets and pre-lubricating bags. Viscosity = 5400 - 7400 cSt
- Multi** All-purpose lubricant. Intermediate viscosity between PHD and HD. Viscosity = 4500 - 6500 cSt
- PHD** Pourable lubricant for medium weight & lighter cable installations. Viscosity = 1800 - 3500 cSt
- M** Specially designed lubricant with microspheres for the Telecoms industry. Viscosity = 1800 - 3500 cSt
- FO** Fiber optic and sub-duct installation lubricant with high elasticity for reduced consumption. Viscosity = 1600 - 3000 cSt