



House Service Cut Outs

- Accepts fuse links to BS1361 maximum rating - TYPE IIa fuse 60/80amp / TYPE IIb fuse 100amp.
- Tested and approved to EA12-10 / BS7657.
- Solid brass terminal blocks with serrated bores and two screws per conductor.
- Accepts conductors up to 35mm²
- Moulded in light grey glass reinforced polyester DMC thermoset material.
- Busbar facility to interconnect cut outs.



Single Pole House Service Cut Out

Ref Code	Description	
SP 100	Single Pole	100amp max
SP 60 / 80	Single Pole	80amp max

Can be used in conjunction with CNE cut out to form TPNE set

Single Pole, Separate Neutral & Earth House Service Cut Out

Ref Code	Description	
SPNE 60 / 80	SP / N&E Cut Out	80amp max
SPNE 100	SP / N&E Cut Out	100amp max
SPNECC	Cable Cover for the above	

Triple Pole, Separate Neutral & Earth House Service Cut Out

Ref Code	Description	
TPNE 60 / 80	TP/N Cut Out	80amp max
TPNE 100	TP/N Cut Out	100amp max
TPNECC	Cable Cover for the above	

Single Pole, Combined Neutral & Earth House Service Cut Out

Ref Code	Description	
SPN 60 / 80	SP & NE Cut Out	80amp max
SPN 100	SP & NE Cut Out	100amp max
SPNCC	Cable Cover for the above	

Triple Pole, Combined Neutral & Earth House Service Cut Out

Ref Code	Description	
TPN 60 / 80	TP/N Cut Out	80amp max
TPN 100	TP/N Cut Out	100amp max
TPNCC	Cable Cover for the above	