

Scottish Power Approved Low Voltage Resin Filled Joints

Features:

- Generous dimensions to accommodate modern mechanical connectors supplied with the kits.
- Clear and detailed drawing-based installation instructions.
- Mechanical connectors supplied requires no special tooling.
- Insulating piercing connectors incorporating on the mains service connections reduce cable preparation times.



Standards: Connectors designed to:

- BS4579 Part 1 and Part 3.
- Engineering Recommendations C79.
- BS EN 61238-1.

Resin filled joints & connectors type tested to:

- Engineering Recommendations C81/ BS7888:part3:1998.
- BS EN 50393:2006.

Kits currently available cover the popular polymeric applications and are as follows:

Kit Ref	SP Code	SP Kit Ref	Description	Resin Volume in Litres
TLNK-SE1-SP01	C12058000	01	Service stop-end for CNE single-phase cable 4-35mm ² (without earth lead)	1.2
TLNK-SE1-SP02	C12058001	02	Service stop-end for single-phase SNE cable 4-35mm ² (without earth lead)	1.2
TLNK-SE3-SP03	C12058002	03	Service stop-end for 3-phase CNE/Waveconal cable 16-35mm ² (without earth lead)	2.2
TLNK-SE3-SP04	C12058003	04	Service stop-end for 3-phase SNE cable 16-35mm ² (without earth lead)	2.2
TLNK-SS1-SP07	C12058010	07	Service straight joint for single-phase CNE/SNE cable 4-35mm ²	2.6
TLNK-SS3-SP08	C12058011	08	Service straight joint for 3-phase CNE/SNE cable 16-35mm ²	2.2
TLNK-SB1-SP11	C12058020	11	Cut/test/re-make or branch joint base kit for single-phase CNE/SNE service cable 4-35mm ²	2.2
TLNK-SB3-SP12	C12058021	12	Cut/test/re-make or branch joint base kit for 3-phase CNE/SNE service cable 16-35mm ²	5
TLNK-MSB-SP14	C12058040	14	Mains-service branch joint for 3-core waveform main 70-185mm ² to up to 2 single-phase CNE/SNE service cable 4-35mm ² (additional phase connectors required for 4-core and/or more than 2 service core connections)	10
TLNK-MSB-SP15	C12058041	15	Mains-service branch joint for 3-core waveform main 240-300mm ² to up to 2 single-phase CNE/SNE service cable 4-35mm ² (additional phase connectors required for 4-core and/or more than 2 service core connections)	16
TLNK-MMS-SP19	C12058050	19	Mains straight joint for 3-core waveform cable up to 95mm ²	10
TLNK-MMS-SP20	C12058051	20	Mains straight joint for 3-core waveform cable up to 185mm ²	15
TLNK-MMS-SP21	C12058052	21	Mains straight joint for 3-core waveform cable up to 300mm ²	21.5
TLNK-MMS-SP22	C12058053	22	Mains straight joint for 4-core waveform cable up to 95mm ²	10
TLNK-MMS-SP23	C12058054	23	Mains straight joint for 4-core waveform cable up to 185mm ²	15
TLNK-MMS-SP24	C12058055	24	Mains straight joint for 4-core waveform cable up to 300mm ²	21.5
TLNK-MMS-SP25	C12058056	25	Mains straight joint for 3-core to 4-core waveform cable up to 95mm ²	10
TLNK-MMS-SP26	C12058057	26	Mains straight joint for 3-core to 4-core waveform cable up to 185mm ²	15
TLNK-MMS-SP27	C12058058	27	Mains straight joint for 3-core to 4-core waveform cable up to 300mm ²	21.5
TLNK-MMB-SP34	C12058070	34	Mains branch joint for 3-core waveform cable up to 95mm ²	18
TLNK-MMB-SP35	C12058071	35	Mains branch joint for 3-core waveform cable up to 185mm ²	24
TLNK-MMB-SP36	C12058072	36	Mains branch joint for 3-core waveform cable up to 300mm ²	29
TLNK-MMB-SP37	C12058073	37	Mains branch joint for 4-core waveform cable up to 95mm ²	18
TLNK-MMB-SP38	C12058074	38	Mains branch joint for 4-core waveform cable up to 185mm ²	24
TLNK-MMB-SP39	C12058075	39	Mains branch joint for 4-core waveform cable up to 300mm ²	29
TLNK-MMB-SP40	C12058076	40	Mains branch joint for 3-core waveform branch to 4-core waveform main up to 95mm ²	18
TLNK-MMB-SP41	C12058077	41	Mains branch joint for 3-core waveform branch to 4-core waveform main up to 185mm ²	24
TLNK-MMB-SP42	C12058078	42	Mains branch joint for 3-core waveform branch to 4-core waveform main up to 300mm ²	29
TLNK-MSE-SP52	C12058093	52	Mains stop-end for 3-core waveform cable up to 95mm ² with PME connector and earth lead	5
TLNK-MSE-SP53	C12058094	53	Mains stop-end for 3-core waveform cable up to 185-300mm ² with PME connector & earth lead	7.2
TLNK-MSE-SP54	C12058095	54	Mains stop-end for 4-core waveform cable up to 95mm ² with PME connector and earth lead	5
TLNK-MSE-SP55	C12058096	55	Mains stop-end for 4-core waveform cable up to 185-300mm ² with PME connector & earth lead	7.2

Please Note: Joint kits do not include resin

NOTE: Customers should satisfy themselves that they have Scottish Power approval to install these joints on the Scottish Power network. Other DNO approved versions of many of these joints are also stocked.