



Heavy Duty Cut Outs - GF400CN

- Lucy glass reinforced plastic 400amp cut out to Central Network approved specification 0620068009.
- Maximum cable size 185mm² (other versions and ratings available).



Insulated Connector Boxes

Type 1 - Single Pole model, manufactured from Phenolic. Block can accept up to a maximum of 4 conductors, copper only. Features include shrouded entries with knockouts protected by shields and slotted-headed pinching screws.

Ref Code	Rating	Number & Size of Conductors (mm ²)		Approx. Dimensions (mm)			Terminal Screw Fitting	
		Minimum	Maximum	Length (Box Only)	Length (Inc Shield)	Width		Depth
54341-15	30amp	4 x 2.5	4 x 16	38	48	33	29	Slotted
54342-18	60amp	4 x 2.5	4 x 25	46	56	40	32	Slotted

Type 2 - (BS7657 Type C1) Single Pole model, manufactured in glass reinforced polyester. Accepts up to 5 conductors, either copper or aluminium. Features include shrouded cable entries with knockouts and a choice of slotted or socket headed pinching screws. *Separate adhesive earth label, branded 'E' lid alternative for earth conductors.

All blocks have sharply serrated bores and flat bottomed pinching screws for stable contact on all conductor types.

Ref Code	Rating	Number & Size of Conductors (mm ²)		Approx. Dimensions (mm)			Terminal Screw Fitting
		Minimum	Maximum	Length	Width	Depth	
54347-37	100amp	5 x 2.5	5 x 35	78	54	35	Socket
54347-38	100amp	5 x 2.5	5 x 35	75	54	35	Slotted
54347-15*	100amp	5 x 2.5	5 x 35	75	54	35	Socket
54347-16*	100amp	5 x 2.5	5 x 35	75	54	35	Slotted

Type 3 - Single Pole model, manufactured in glass reinforced polyester. Accepts up to 5 conductors, either copper or aluminium. Features include wood bush for top and bottom entry, slotted-headed pinching screws. Blocks have serrated bores and flat bottomed pinching screws.

Ref Code	Rating	Number & Size of Conductors (mm ²)		Approx. Dimensions (mm)			Terminal Screw Fitting
		Minimum	Maximum	Length	Width	Depth	
54473-03	200amp	5 x 2.5	5 x 70	137	68	54	Slotted

Type 4 - Single Pole & Neutral model, manufactured from glass reinforced polyester. Block can accept up to 5 conductors, copper only. Features include separate phase and neutral compartments; identification of neutral block, choice of socket or slotted headed pinching screws.

Ref Code	Rating	Number & Size of Conductors (mm ²)		Approx. Dimensions (mm)			Terminal Screw Fitting
		Minimum	Maximum	Length	Width	Depth	
54344-03	100amp	5 x 2.5	5 x 25	52	93	48	Slotted
54344-04	100amp	& 2 x 2.5	& 2 x 16	52	93	48	Socket

All connector boxes are supplied with: (1) Fixing screws for wood or chipboard.
(2) Sealing tag/s (for types 1, 2 and 4 only).
(3) Sealing screws for lid fixing (type 3 only).

Lucy versions and uninsulated brass terminal blocks available.