



Fuse Units Titan 2 Unit

The Titan 2 range provides improved flexibility and will be the only unit available that gives the extensive range of options required by installers.

Specification:

- Designed, manufactured in accordance with BS7654 and IEC947 Pt1.
- Clear access gear tray for enhanced access.
- Terminal blocks to accept circular conductors up to 25mm².
- Cable entry plates in plastic or brass.
- Sealing wire and padlock facilities available.
- IP43 rating.
- Standard unit: Height 150mm / Width 81mm / Depth 65mm.
- Various extension troughs available to provide additional space when terminating larger or multiple cables.



Option Available:

Single Phase, Single Pole, Loop In / Out, Single Fuse	(Type NT02)
Single Phase, Single Pole, Loop In / Out, Two Fuse	(Type NT04)
Single Phase, Single Pole, CNE (REC version)	(Type NT15)
Single Phase, Double Pole, Loop In / Out, Single Fuse	(Type NT06)
Single Phase, Double Pole, Loop In / Out, Two Fuse	(Type NT08)
Single Phase, Double Pole, Loop In / Out, with Fused Double Pole Spur	(Type NT10)
Three Phase, Double, Loop In / Out, Single Fuse	(Type NT12)
Three Phase, Double, Loop In / Out, Two Fuse	(Type NT14)

Titan Extension Troughs

Various extension troughs available to provide additional space when terminating larger or multiple cables.

