

# FMT CONSTANT WATTAGE PARALLEL HEATING CABLE



nVent RAYCHEM FMT constant wattage parallel trace heating cables provide freeze protection and process temperature maintenance, up to 150 °C. They can withstand routine steam purges and intermittent exposure to 200 °C, 230 V supply and FEP outer jacket. Approved for use in hazardous areas.

### **FEATURES & BENEFITS**

Fast installation: round geometry, cut-to-length, meter markings, user-friendly connection kits

Safe and efficient in operation, energy saving technology

Extended circuit lengths, available in 230 V and 400 V versions

Reliable during long life: 10 year extended product warranty available, maintenance free

## **SPECIFICATIONS**

Max Continuous Exposure Temperature, Power Off 200 °C

Outer Jacket Material FEP

Area Classification Hazardous

Min Installation Temperature  $-40~^{\circ}\text{C}$ 

Min Bending Radius 25 mm

Min Clearance 50 mm

Outer Diameter 7.5 mm

Nominal Cold Lead/Heating Zone Length 1.5 m

Table 1/1			
Catalog Number	Item Name	Nominal Power Output @ 230V	Max Power Output @ 230V
1244-006057	10FMT2-CT	10 W/m	12.7 W/m
1244-006058	20FMT2-CT	20 W/m	25.5 W/m
1244-006059	30FMT2-CT	30 W/m	38.2 W/m

# North America

Tel +1.800.545.6258 Fax +1.800.527.5703 thermal.info@nvent.com

### Europe, Middle East, Africa

Tel +32.16.213.511 Fax +32.16.213.604 thermal.info@nvent.com

#### **Asia Pacific**

Tel +86.21.2412.1688 Fax +86.21.5426.3167 cn.thermal.info@nvent.com

#### **Latin America**

Tel +1.713.868.4800 Fax +1.713.868.2333 thermal.info@nvent.com



Our powerful portfolio of brands:

**nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER**