

# **GLAND**



nVent RAYCHEM GL-xx are a range of cable glands for use with various size armoured or non-armoured power cables. The glands are available in different sizes and materials and are approved for use in hazardous areas.

## **FEATURES & BENEFITS**

Available in different sizes and materials

Approved for use in hazardous areas

## **SPECIFICATIONS**

Thread Type  $\, \mathsf{NPT} \,$ 

Area Classification Non-Hazardous; Hazardous

Table 1/2						
Catalog Number	Item Name	Material	Finish	IP Rating	Ambient Temperature	Thread Size
1244-017517	GL-33	Brass	Nickel-Plated	IP66	-60 to 140 °C	3/4"
1244-017518	GL-34	Brass	Nickel Plated	IP66	-60 to 140 °C	3/4"

Table 2/2					
Catalog Number	Item Name	Locknut Included	For Armored Cable		
1244-017517	GL-33	No	Yes		

Catalog Number	Item Name	Locknut Included	For Armored Cable
1244-017518	GL-34	No	No

## Thread Type Metric

Area Classification Non-Hazardous; Hazardous

Table 1/2						
Catalog Number	Item Name	Material	Finish	IP Rating	Ambient Temperature	Thread Size
056622-000	GL-38-M25- METAL	Brass	Nickel-Plated	IP66	-60 to 140 °C	M25
1244-019083	GL-55-M25	Polyamide	Untreated	IP66	-55 to 70 °C	M25
1244-019082	GL-36-M25	Polyamide	Untreated	IP66	-20 to 70 °C	M25
1244-000847	GL-45-M32	Polyamide	Untreated	IP66	-55 to 70 °C	M32
1244-007003	GL-51-M40	Polyamide	Untreated	IP66	-55 to 70 °C	M40

Table 2/2					
Catalog Number	Item Name	Locknut Included	For Armored Cable		
056622-000	GL-38-M25-METAL	Yes	Yes		
1244-019083	GL-55-M25	No	No		
1244-019082	GL-36-M25	No	No		
1244-000847	GL-45-M32	No	No		
1244-007003	GL-51-M40	No	No		

#### **North America**

Tel +1.800.545.6258 Fax +1.800.527.5703 thermal.info@nvent.com

#### Europe, Middle East, Africa

Tel +32.16.213.511 Fax +32.16.213.604 thermal.info@nvent.com

#### **Asia Pacific**

Tel +86.21.2412.1688 Fax +86.21.5426.3167 cn.thermal.info@nvent.com

#### **Latin America**

Tel +1.713.868.4800 Fax +1.713.868.2333 thermal.info@nvent.com



Our powerful portfolio of brands:

**nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER**