

REDUCER

nVent RAYCHEM Adapters/Reducers are available in different materials, to suit a wide range of applications.



FEATURES & BENEFITS

Multiple combinations

Available in various materials

Variants available with approval for use in hazardous areas

SPECIFICATIONS

Material Brass

Hazardous Area Approved Yes

Table 1/1

Catalog Number	Item Name	IP Rating	Ambient Temperature	Male	Female
630617-000	REDUCER-M25/20	IP66	-50 to 180 °C	M25	M20
404287-000	REDUCER-M25/20-EEXD	IP66	-50 to 180 °C	M25	M20

Material Polyamide

Hazardous Area Approved Yes

Table 1/1

Catalog Number	Item Name	IP Rating	Ambient Temperature	Male	Female
953780-000	REDUCER-M25/PG16-EEXE	IP66	-20 to 40 °C	M25	PG16
1244-000859	REDUCER-M32/M25-EEXE	IP66	-55 to 70 °C	M32	M25
1244-007007	REDUCER-M40/M32-EEXE	IP66	-55 to 70 °C	M40	M32

Material Stainless Steel

Hazardous Area Approved Yes

Table 1/1

Catalog Number	Item Name	IP Rating	Ambient Temperature	Male	Female
1244-000953	REDUCER-1NPT/M25	IP6X	-50 to 180 °C	1" NPT	M25
414478-000	REDUCER-1NPT/PG16-EEXD	IP64 - 68 (Installation Dependent)	-50 to 180 °C	1" NPT	PG16
1244-002090	REDUCER-M25/M20-EEXD-SS	IP66	-50 to 100 °C	M25	M20

North America

Tel +1.800.545.6258
Fax +1.800.527.5703
thermal.info@nvent.com

Europe, Middle East, Africa

Tel +32.16.213.511
Fax +32.16.213.604
thermal.info@nvent.com

Asia Pacific

Tel +86.21.2412.1688
Fax +86.21.5426.3167
cn.thermal.info@nvent.com

Latin America

Tel +1.713.868.4800
Fax +1.713.868.2333
thermal.info@nvent.com



Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

© 2021 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.
nVent reserves the right to change specifications without notice.