

TM10 MECHANICAL THERMOSTAT



nVent RAYCHEM T-M-10-S/+x+y is a non-hazardous area mechanical surface sensing thermostat providing temperature control for heating cables. Available in ranges: 0 °C-50 °C; 0 °C-200 °C; 50 °C-300 °C. The temperature set point can be adjusted without opening the enclosure via a removable plug in the lid. Direct connection of the heating cable is possible, switching current capacity is 16 A.

FEATURES & BENEFITS

Simple to install and operate: supplied with 2 m long stainless steel fluid filled capillary, 2 cable entries

Energy saving, line-sensing electronic control thermostat

Adjustable set point in ranges: 0 °C-50 °C; 0 °C-200 °C; 50 °C-300 °C (without opening the enclosure via a removable plug in the lid)

Direct switching, maximum current 16 A, 230 VAC: single pole change-over with volt-free contacts, SPDT

Lightweight unit, can be pipe mounted using nVent RAYCHEM support brackets or surface mounted

SPECIFICATIONS

Material Glass Fiber Reinforced Polymer

Thermostat Type Mechanical Thermostat

Current Rating 16 A

Height 120 mm

Width 122 mm

Depth 90 mm

Table 1/1

Catalog Number	Item Name	Controller Temperature Setting
337388-000	T-M-10-S/0+200C	0 – 200 °C
607672-000	T-M-10-S/+50+300C	50 – 300 °C
105336-000	T-M-10-S/0+50C	0 – 50 °C

North America

Tel +1.800.545.6258
 Fax +1.800.527.5703
thermal.info@nvent.com

Europe, Middle East, Africa

Tel +32.16.213.511
 Fax +32.16.213.604
thermal.info@nvent.com

Asia Pacific

Tel +86.21.2412.1688
 Fax +86.21.5426.3167
cn.thermal.info@nvent.com

Latin America

Tel +1.713.868.4800
 Fax +1.713.868.2333
thermal.info@nvent.com



Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

© 2021 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.
 nVent reserves the right to change specifications without notice.