

## PRODUCT DATA SHEET

## TRENCHTAPE™ UNDERGROUND WARNING TAPE

**UKT05** 

Ref	TS235
Date	March 2023
Pages	1 of 1

**DESCRIPTION** Self-coloured, high-visibility plastic tape overprinted with a warning identification text. Designed to

mark the position of buried utility lines to help reduce the risk of third party damage. Made from 100% virgin polyethylene with high acid & alkali resistance, with a life expectancy in excess of 40 years.

Manufactured free from PVC.

INSTRUCTIONS / USES For best results, the tape should be installed as close to the ground surface as possible. We recommend

that due consideration is given to the NJUG guidelines, although a typical installation would see a utility line buried at a depth of 600mm then the trench backfilled by 300mm and the tape laid directly on top

i.e 300mm below the ground surface.

**BENEFITS / KEY FEATURES** > 40-year life underground

> Advanced-grade, lead-free linear low-density polyethylene

> UK Tapes Ltd - proven reliability since 1996

SUBSTRATE	INK	CORE
Virgin Grade LDPE (linear low density polyethylene)	Highly resistant, solvent based	76mm diameter cardboard core
TAPE WIDTH	TAPE THICKNESS	ROLL LENGTH
150mm wide	50mu (0.05mm)	365M long
PVC CONTENT	RESISTANCE TO ACID	RESISTANCE TO ALKALI
The tape contains NO PVC	Highly resistant	Highly resistant
ELONGATION	ROLL WEIGHT	CARTON QUANTITY
300%	Approx 2.0 kgs	10 rolls

OTHER INFORMATION The tapes comply with the applicable parts of the following specifications

BS2782 (testing) BS381c (colours) BS3012 (plastics)

NJUG 4 Identification of small buried mains & services

NJUG 7 Recommended positioning of utilities

NJUG 9 Guidelines on positioning & colour coding of utilities

In addition, the tapes comply with various specifications for non-UK countries – please contact our sales department for further information.

BASE COLOUR	PRINT COLOUR	DESIGN
Various	Various	Various